

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

**EP 0 947 446 A1**

(12)

**EUROPEAN PATENT APPLICATION**(43) Date of publication:  
06.10.1999 Bulletin 1999/40(51) Int. Cl.<sup>6</sup>: B65D 85/16, B65D 77/02,  
B65B 63/04, A61F 15/00,  
A61F 13/15

(21) Application number: 99109918.5

(22) Date of filing: 04.03.1997

(84) Designated Contracting States:  
DE ES FR GB IT NL SE

(30) Priority: 15.03.1996 SE 9600996

(62) Document number(s) of the earlier application(s) in  
accordance with Art. 76 EPC:  
97908622.0 / 0 938 437(71) Applicant:  
SCA Hygiene Products AB  
405 03 Göteborg (SE)(72) Inventor: Mattlasson, Marina  
416 67 Göteborg (SE)(74) Representative:  
Hyttner, Jan-Olof  
Göteborgs Patentbyrå Dahls AB  
Box 606  
182 16 Danderyd (SE)Remarks:This application was filed on 20 - 05 - 1999 as a  
divisional application to the application mentioned  
under INID code 62.(54) **Method of package-folding an absorbent article**

(57) The present invention relates to a method of package-folding an absorbent article, such as a diaper or an incontinence guard, comprising a rear part (5), a front part (4), an intermediate crotch part (6), and an absorbent body (1) enclosed between casing sheets (2, 3). According to the invention, laterally projecting parts of the article are folded inwards so as to give the article a rectangular shape, whereafter at least longitudinally outer portions of the rear front parts (5, 4) of the article are folded in towards the crotch part (6). The invention also relates to a package-folded absorbent article, and to packaging of a bundle of package-folded articles.

EP 0 947 446 A1

1

EP 0 947 446 A1

2

**Description**

[0001] The present invention relates to a method of package-folding an absorbent article, such as a diaper or an incontinence guard, that comprises a rear part, a front part, an intermediate crotch part, and an absorbent body enclosed between enveloping casing sheets. The invention also relates to a package-folded article and to a package comprising a compressed bundle of such package-folded articles.

[0002] Absorbent articles of the aforesaid kind are normally folded together to form a rectangular shape and then double-folded prior to being packaged. One drawback with folding the articles in this way, is that folding is effected in the crotch part of the article, which is often the most sensitive part of the absorbent body. After package-folding the articles, the articles are bundled and then compressed so as to reduce the bundle volume, prior to inserting the bundle into a bag or like packaging unit made of flexible material. This compression significantly reduces the volume of the bundle of articles. The packaged articles therewith take up much less transport space and storage space than would be the case if the articles were not compressed. However, the compressed packaged articles strive to return to their original thickness and therewith press against the walls of the package and against each other with a relatively large force. The pressure thus exerted by the packaged articles can make it difficult to remove the first articles from a package. This problem has been solved traditionally, by providing one of the walls of the package with relatively large tear-away pieces; see for instance EP-A2-0,349,050 and EP-B1-0,554,411. Removal of these relatively large tear-away pieces leaves relatively large openings through which parts of package-folded articles are able to fan-out, because expansion of these parts of the articles can no longer be prevented by the package wall. An opened package will therewith require more space than an unopened package.

[0003] The object of the present invention is to eliminate the aforesaid drawbacks and to provide a packaging unit for compressed absorbent articles in which the articles are positively retained even when the package is opened, and from which articles can be easily taken.

[0004] These objects are achieved in accordance with the invention by means of a method of the kind defined in the introduction and characterized by inwardly folding laterally projecting parts of the article, such as to give the article a rectangular shape, and thereafter folding outer portions of the rear and the front parts of the article inwardly towards the crotch part thereof, at least in the longitudinal direction of the article.

[0005] In a preferred embodiment of the method, only portions of casing material that lie outside the absorbent body are folded in towards the crotch part of the article.

[0006] The invention also relates to a package-folded absorbent article, such as a diaper or an incontinence guard, that comprises a rear part, a front part, an inter-

mediate crotch part, and an absorbent body enclosed between enveloping casing sheets, wherein the article is characterized in that portions of the rear and the front parts thereof are folded in towards the crotch part, at least in the longitudinal direction of the article; and in that the absorbent body is left unfolded in the crotch part. By folding at least outer portions of the front and the rear parts of the article in towards the crotch part, it can be ensured that the top and bottom sides of the package-folded article will remain straight irrespective of the outer contours of said front and rear article parts, at the same time as the absorbent body will remain in its original non-deformed state in the crotch part.

[0007] In a preferred embodiment, at least one of the front and the rear parts of the article has an outer edge-part of casing material located outwardly of the absorbent body, this outer edge-part overlapping a portion of the other of said front or rear article parts in the package-folded state of said article.

[0008] The invention also relates to a flexible packaging unit for accommodating at least one compressed bundle of absorbent articles, such as diapers or incontinence guards, each including a rear part, a front part, an intermediate crotch part and an absorbent body enclosed between enveloping casing sheets, said articles being folded so that outer portions of the front and the rear parts will be folded-in towards the crotch part, at least in the longitudinal direction, and face in one and the same direction in a respective bundle, said packaging unit embracing the bundle or stack of articles and having a generally parallelepipedic shape that includes an upper side, a lower side, two mutually opposing side walls and two mutually opposing end walls, and package-unit opening means which enable the unit to be opened so that articles can be taken therefrom, wherein the packaging unit is characterized in that the package-unit opening means comprises an opening-forming part on the end wall towards which the inwardly folded portions of the front and rear parts of the articles in said bundle face, wherein the opening-forming part extends parallel with the front and rear edges of the inwardly folded front and rear article parts and can be moved out of the plane of said end wall and has a position and a width such that at least one of the outer edges of the front or the rear article part will be exposed when the opening-forming part is moved out of the plane of said end wall.

[0009] In a preferred embodiment, at least one of the front and the rear article parts includes a longitudinally outer edge-part of casing material located outwardly of the absorbent body, said edge-part overlapping a portion of the upper of said front or rear article parts in the packaged-folded state of the article, wherein said opening-forming part extends along the edge of said outer edge-part of the casing material. The opening-forming part has a smallest width of 10 mm and a largest width corresponding to 33% of the length of a package-folded article and is defined by two mutually parallel weaken-

3

EP 0 947 446 A1

4

ing lines that extend over the full width of the end wall, from one side wall to the other. The parallel weakening lines extend slightly into the side walls and a further weakening line is provided in one of the side walls, between the ends of the parallel weakening lines.

[0010] The invention will now be described in more detail with reference to the accompanying drawings, in which

Figs. 1 to 4 are schematic views illustrating the different steps in package-folding a diaper in accordance with the invention from above;

Fig. 5 is a side view of the diaper shown in Fig. 4;

Figs. 6 and 7 illustrate schematically the introduction of a bundle of package-folded diapers into a packaging unit according to a first embodiment of the invention;

Fig. 8 is a schematic perspective view of an opened packaging unit;

Figs. 9 to 12 are schematic side views with one side wall removed and show the different stages of removing a diaper from an opened packaging unit; and

Fig. 13 illustrates an end wall provided with an opening-forming means in accordance with a second embodiment of the invention.

[0011] Fig. 1 illustrates from above a diaper with which the invention can be conveniently applied. The illustrated diaper includes an hourglass-shaped absorbent body 1 enclosed between two similarly shaped casing sheets 2, 3, which are joined together along parts thereof that lie outwardly of the absorbent body 1. The lateral extension of the front and rear parts 4 and 5 of the diaper is greater than that of the intermediate crotch part 6. The diaper also includes side bodies 7, 8, and elastic threads or bands 9, 10 along the long edges of the crotch part. The side bodies 7, 8 function to stabilize the three-dimensional shape of the diaper when in use, and it is desirable that these side bodies are deformed to the least possible extent when packaging the diaper after its manufacture.

[0012] It will be noted that by the longitudinal direction of the absorbent article is meant a direction that extends from the front part of the diaper to its rear part, irrespective of whether the article is package-folded or not, and irrespective of whether its lateral extension is greater than its longitudinal extension.

[0013] The diaper illustrated in Figure 1 is brought to its packaging state, i.e. package-folded, by folding the parts of the casing sheets that lie laterally outside the bodies 7, 8 in over the central parts of the diaper. Figure 2 shows the configuration of the diaper after having

folded-in the left-hand parts of the casing sheets, while Figure 3 illustrates the rectangular shape of the diaper after having folded-in the right-hand parts of said sheets.

[0014] According to the invention, the front-part 4 of the article is first folded-in towards the crotch part 6 and thereafter the rear part 5, along respective transverse fold lines A and B located immediately outside the outer longitudinally extending defining points of the side bodies 7, 8. The diaper then has the configuration shown from above and in side view respectively in Figures 4 and 5. Neither the parts of the absorbent body 1 lying in the crotch part nor the side bodies 7, 8 will be affected by package-folding the diaper. A package-folded diaper of the type shown in Figure 1 is referenced 11 in Figures 4 and 5.

[0015] Naturally, package-folding of the diaper in accordance with the invention can be effected by folding-in the rear part before folding-in the front part of the diaper.

[0016] It will also be understood that the aforesaid folding procedure can be applied with other types of absorbent articles with which it is desirable for the crotch parts of the absorbent bodies to remain in their original unfolded state or to include central non-folded parts, for one reason or another.

[0017] In the configuration illustrated in Figures 4 and 5, the inwardly folded front and rear edges of the absorbent body 1 are mutually contiguous, i.e. touch one another. However, the edge portions of the absorbent body may be folded inwardly so as to be spaced from one another instead. For instance, this latter alternative may be appropriate when parts of the diaper which are desired to be left non-folded after package-folding the diaper would be affected by package-folding with the inwardly folded edges of the absorbent body lying edge to edge.

[0018] It is also convenient to package-fold in accordance with the invention articles whose absorbent bodies have curved outer contours at the front and/or the rear parts of said bodies, therewith to achieve packaging of the articles in a generally parallelepipedic shape.

[0019] Figures 6 and 7 illustrate schematically packaging of a bundle of diapers 11 that have been package-folded to the configuration shown in Figures 4 and 5. In the Figure 6 illustration, the diaper bundle has been compressed, e.g. by holding the bundle between the arms of a gripping tool and then moving the arms towards one another until the bundle has been compressed to the extent desired. The volume of a compressed diaper bundle may be half of the volume of the bundle prior to its compression. Compression of the bundle of diapers 11 is symbolized by hollow arrows in Figure 6.

[0020] The compressed bundle of diapers 11 is inserted in some suitable manner, e.g. with the aid of the aforesaid gripping tool, into a packaging unit 12 through the open bottom thereof, as indicated by the full

5

EP 0 947 446 A1

6

arrow in Figure 6. The open bottom of the packaging unit 12 is then closed and sealed, for instance by ultrasonic welding or heat welding when the packaging material is weldable, or by gluing, so as to obtain a parallelepipedic package. One such closed packaging unit 12 is shown in Figure 7. The packaging unit 12 has an upper side 13, an underside or bottom 14, two mutually opposing side walls 15, of which only one is shown in Figures 6-8, and two mutually opposing end walls 16, 17. The bundle of diapers 11 introduced into the packaging unit presses against the end walls 16, 17 and the side walls 15 are thereby subjected to a force acting in the direction of the double arrow in Figure 7. Extending across the end wall 16 are two parallel lines of perforations 18, 19, which also extend slightly into the side walls 15. A further perforated line 20 extends along the side wall 15 that faces towards the viewer of Figure 7, between the ends of the perforated lines 18, 19. The three perforated lines 18-20 together define a tear-off strip 21.

[0021] Figures 8 and 9 show the packaging unit 12 with the strip 21 torn from the end wall 16, so as to open the package. The strip 21 is suitably left connected to the side wall that cannot be seen in the Figure. As illustrated in Figures 8 and 9, the opening created by tearing of the strip 21 is located opposite the end edge 22 of the inwardly folded rear part of the first diaper 11 present in the bundle. As a result of the compressive force acting on the diaper, said end edge will be pressed out through the opening and capable of being gripped by a user.

[0022] The removal of a diaper from an opened package 12 is illustrated schematically in Figures 9-12. A diaper 11 is removed from the package, by gripping the end edge 22 accessible through said opening and then drawing said end edge downwards as indicated by arrows in Figures 9 and 10. When the upper part of the diaper has been drawn from the package, the direction in which the diaper is pulled from the package is conveniently changed, as indicated by an arrow in Figure 11. It has been found that it is easier to remove a first diaper from an inventive packaging unit than from a known packaging unit in which the diapers are exposed in a fan-like configuration.

[0023] Figure 12 illustrates the package 12 after having removed the first diaper 11 from the diaper bundle. As will be seen from this Figure, the package has an appearance which is identical to its appearance before removing the first diaper, due to the slight expansion of the remaining diapers which therewith fill up the empty space left by the first diaper removed. The pressure on the end walls 16, 17 will, however, have decreased slightly.

[0024] Although the bundle of package-folded articles are inserted through the open bottom of the packaging unit and the bottom then closed and sealed in the case of the illustrated embodiment, it will be understood that the packaging unit may be given an open top and the bundle of diapers introduced through the top of the

packaging unit instead. In this latter case, an article is removed by first pulling said end edge upwards and then downwards principally in the same way as that shown in Figures 9-12 when these Figures are turned upside down.

[0025] The width of the strip 21, i.e. the vertical extension of the strip as seen in the Figures, can vary within relatively wide limits. However, the strip 21 will preferably have a smallest width of 10 mm, so as to enable the end edge 22 to be readily gripped. The upper limit of the width of the strip is determined by the need to ensure that the diapers will be retained safely in the opened package, meaning that the end wall 16 must extend unbroken from the upper side and lower side of the package 12 to some extent. The maximum width of the strip 21 shall not therefore exceed 33% of the vertical extension of the end wall 16.

[0026] Figure 13 illustrates a second embodiment of an inventive packaging unit. The sole difference between the packaging unit shown in Figure 13 and the packaging unit shown in Figures 6-12 is that the opening-forming means 21' is different to the strip 21 of the embodiment shown in Figures 6-8. The whole of the opening-forming means 21' is disposed in the end wall 16' of the packaging unit 12' and is defined by a horizontal perforated line 23 and two vertical perforated lines 24, 25 which extend parallel with the side walls of the packaging unit 12', close to the side edges of said end wall. When opening the means 21', there are formed two outwardly folded flaps between which the end of a package-folded article will protrude.

[0027] The embodiment illustrated in Figure 13 can be modified in several ways. For instance, the horizontal perforated line 23 may extend between opposing top and bottom ends of the vertical lines 24, 25. Furthermore, the vertical lines may be provided in the side walls, similar to the lines 20 in Figures 6-8. It will be understood in this regard, that the lines 20 may be provided in the end wall 16 instead of in the side walls, analogously with the lines 24, 25.

[0028] It is preferred that the opening obtained in the packaging unit has a width greater than 10 mm, suitably greater than 20 mm, conveniently greater than 30 mm and most preferably greater than 40 mm. Trials have shown that a width of 50 mm is extremely effective, and it is accordingly preferred that the opening will have a width of about 50 mm or a width that corresponds to 33% of the length of a package-folded article, depending on which of these measurements is the smallest.

[0029] It will be understood that the described and illustrated embodiments of the invention can be varied within the scope of the inventive concept, particularly with regard to the shape or configuration of the absorbent articles. Furthermore, other types of weakening lines than perforated lines can be used to define the tear-off strip. The packaging unit may also contain more than one bundle of articles placed horizontally adjacent one another and/or stacked on top of one another.

7

EP 0 947 446 A1

8

When the bundles are placed horizontally adjacent one another, the tear-off strip may conveniently be common to mutually adjacent bundles, therewith facilitating manufacture of such a packaging unit. Furthermore, the openable part of the end wall may be provided at the opening-forming end with a grip tab or the like to facilitate opening of the packaging unit. The invention is therefore restricted solely by the contents of the following Claims.







#### Claims

1. A method of package-folding a diaper or an incontinence guard, comprising a rear part (5), a front part (4), an intermediate crotch part (6), and an absorbent body (1) enclosed between enveloping casing sheets (2, 3), characterized by inwardly folding laterally projecting portions of the article such as to give the article a rectangular shape, and thereafter folding at least longitudinally outer portions of the rear and the front parts (5, 4) of said article in towards the crotch part (6). 5
2. A method according to claim 1, characterized by folding in towards the crotch part (6) of the article only parts of casing material (2, 3) that lie outside the absorbent body (1) 15
3. A package-folded diaper or incontinence guard, comprising a rear part (5), a front part (4), an intermediate crotch part (6), and an absorbent body (1) enclosed between casing sheets (2, 3), characterized in that at least longitudinally outer portions of the rear and the front parts (5, 4) are folded inwardly towards the crotch part (6); and in that the absorbent body (1) has been left unfolded in the crotch part of the article. 20
4. A diaper or incontinence guard according to Claim 3, characterized in that at least one of the front and rear parts (4, 5) of the article includes a longitudinally outer casing material edge part outwardly of the absorbent body (1), and in that said edge part overlaps part of the other (4) of said front or rear parts (4, 5) of the article in its package-folded state. 25
5. A diaper or incontinence guard according to Claim 3, characterized in that the rear and front parts of the article have been folded so that the front and rear edges of the absorbent body will abut one another. 30


55

5

EP 0 947 446 A1



EP 0 947 446 A1



EP 0 947 446 A1

European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 99 10 9918

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 91 18574 A (PROCTER & GAMBLE) 12 December 1991 (1991-12-12) * page 4, line 20 - page 5, line 21 * * page 10, line 9 - page 12, line 13 *	1-4	B65D85/16 B65D77/02 B65B63/04 A61F15/00 A61F13/15
Y	* page 13, line 36 - page 14, line 19; figures 1-9 *	5	
Y	EP 0 313 426 A (LEBOUGAULT) 26 April 1989 (1989-04-26) * column 4, line 21-63; figures 1-4 *	5	
X	GB 2 273 279 A (KAO) 15 June 1994 (1994-06-15) * page 37, paragraph 4 - page 44; paragraph 1; figures 21,22,24 *	1-4	
A	EP 0 419 770 A (CHRISTIAN SENNIG VERPACKUNGSAUTOMATEN) 3 April 1991 (1991-04-03) * column 2, line 50 - column 3, line 58; figures 1-3 *	5	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B65B B65D A61F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 August 1999	Examiner Lenoir, C
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : member of the same patent family, corresponding document X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document	

EPO FORM 1503 (02.02.99) (P.27/64)



EP 0 947 446 A1

ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 99 10 9918

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-08-1999

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9118574	A	12-12-1991	AT 113195 T	15-11-1994
			AU 661459 B	27-07-1995
			AU 7907491 A	31-12-1991
			CA 2082926 A,C	06-12-1991
			CN 1059695 A	25-03-1992
			CS 9101686 A	15-01-1992
			DE 69104834 D	01-12-1994
			DK 532649 T	28-11-1994
			EG 19258 A	29-09-1994
			EP 0532649 A	24-03-1993
			ES 2062802 T	16-12-1994
			FI 925525 A	04-12-1992
			HK 1006144 A	12-02-1999
			HU 67201 A	28-02-1995
			IE 66183 B	13-12-1995
			KR 9512184 B	14-10-1995
			NZ 238380 A	24-02-1995
			PL 167333 B	31-08-1995
			PT 97851 A,B	31-03-1992
			RU 2088192 C	27-08-1997
			TR 28691 A	16-01-1997
			US 5484636 A	16-01-1996
			US 5569230 A	29-10-1996
			US 5569228 A	29-10-1996
EP 313426	A	26-04-1989	FR 2621815 A	21-04-1989
GB 2273279	A	15-06-1994	GB 2298627 A,B	11-09-1996
			HK 29297 A	21-03-1997
			HK 1002989 A	30-09-1998
			SG 44596 A	19-12-1997
EP 419770	A	03-04-1991	DE 8911486 U	31-01-1991
			CA 2025856 A	28-03-1991
			JP 3148479 A	25-06-1991

EPO FORM P0408

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82